

Patent Application of  
**January Kister**

5

For

**Bundled Probe Apparatus for Multiple Terminal Contacting**

10

**FIELD OF INVENTION**

15

The invention relates to probe apparatus for testing electronic circuit chips. Particularly, the present invention relates to a probe apparatus capable of recognizing and compensating resistance discrepancies in contact interfaces between chip terminals and probe tips.

20

**BACKGROUND OF INVENTION**

25

Before electronic circuit chips are packaged, they are conventionally tested to retrieve information about their performance levels. A performance criterion, for example, are voltage level discrepancies within the tested chip. The continuing development of circuit chips results in an ever decreasing voltage level at which the circuit chips operate and have to be tested. The recognition of voltage level discrepancies at ever decreasing operational voltage

30

levels requires more precise inducing and deriving of test signals during the chip testing. For a cost effective chip fabrication it is at the same time desirable to have a probe apparatus capable of compensating for a broader bandwidth of physical and dimensional tolerances of the chip terminals accessed during the chip testing. On the other hand, the chip testing has to be performed with shortest possible testing times, leaving little time for establishing sufficient contacting quality between the probes and the chip terminals.

The contacting quality is mainly defined by a resistance in an interface between probe tip and chip terminal. To reduce the interface resistance, probes and/or the probe apparatus are commonly configured to scrub slightly along the terminal surface and thereby remove thin insulating oxidation layers. With decreasing sizes of the chip terminals and decreasing terminal surface radii in case of solder bumps or solder balls, scrubbing distances may become shorter. As a result, the removal of oxide layers becomes more difficult to accomplish.

Therefore, there exists a need for a probe apparatus capable of recognizing resistance discrepancies in the probe/terminal interfaces and for correspondingly adjusting a voltage level of a consecutive operational signal applied onto or derived from the chip terminal during the actual chip testing. The present invention addresses this need.

## SUMMARY

A probe apparatus is introduced that provides two or more probes grouped together in order to contact single chip terminals. After bringing the grouped probes into contact with the single chip terminal, the resistance is recognized along the probes, the chip terminal and their interfaces. The grouped probes have a configuration and are assembled in a fashion that prevents them from directly conductively contacting with each other.

The recognized resistance is taken as a factor to compensate for a voltage drop of an operational signal applied onto or derived from the single terminal during the following testing of the circuit chip.

In a first embodiment, two probes are grouped or bundled and are brought into conductive contact with a single chip terminal. The initially recognized resistance is averaged between the two probes and half of the recognized resistance is considered for the voltage drop compensation. One or both probes may be utilized for applying and/or deriving operational signals during the chip testing.

In a second embodiment, three probes are brought into conductive contact with a single chip terminal. In a following procedure three path resistances are recognized; a first path resistance along first and second probe, the chip terminal and their interfaces; a second path resistance along first and third probe, the chip terminal and their interfaces; a third path resistance along second and third probe along the chip terminal. All three path

resistances have a constant resistance portion and a variable resistance portion. The constant resistance portion is predetermined by the physical configuration of the probes and the test terminal. The variable resistance portion results from the configuration of the interface between the probe tips contacting or scrubbing the single terminal as is well known to those skilled in the art. The variable resistance portion changes with each new contacting. The probes themselves may be in a loose contact with terminals of a space transformer as is well known to those skilled in the art. In such a case, the variable resistance portion may include an additional interface resistance in the interface between the upper probe ends and the corresponding terminals of the space transformer.

After recognizing the three path resistances, their constant resistance portion is subtracted and the remaining variable resistance portions of the first, second and third path resistance are compared to each other. Each variable path resistance has two variable path resistance components, each correlated to one of the two interfaces along the test path. The test path is the path of a test voltage applied between the space transformer terminals in order to recognize the three path resistances. The test voltage passes only through the chip terminal and not through the tested circuit chip itself. The test voltage is utilized for testing path resistances, whereas the operational signal is applied and/or derived from the chip terminal and passes through the chip during the chip testing.

In the second embodiment the three variable path resistance components are recognized preferably for each contacted chip terminal after the three unit probes are brought into contact. The three variable path resistance components  
5 form an interweaved relation in three unique combinations of two of them, one unique combination in each of the three path resistances. This interweaved relation is utilized to derive an absolute resistance for each variable path resistance component and consequently an absolute  
10 resistance for a first, second and/or third operational signal path through the first, second and/or third probe onto or away from the chip terminal. As a result, each of the three probes may be utilized for chip testing regardless their eventual diverging variable path  
15 resistance components.

The probes are preferably buckling beams as are well known to those skilled in the art. Grouped probes dedicated for concurrent contacting of single chip terminals and in the  
20 configuration of buckling beams may be bundled and guided in correspondingly shaped sheath holes. In the first embodiment, the sheath holes may have a long hole shape configured to slide able hold two probes in position suitable for contacting the chip terminals. In the second  
25 embodiment, the sheath hole may have a circular shape.

Grouped probes may be held together over their length either in parallel orientation to each other or may be  
30 curled around each other for additional mechanical strength.

## BRIEF DESCRIPTION OF THE FIGURES

**Fig. 1** shows a top view of an exemplary chip terminal placed on a chip segment.

5

**Fig. 2** shows a top view of the chip terminal of **Fig. 1** contacted by two exemplary probe segments according to the first embodiment of the present invention.

10 **Fig. 3** shows a schematic view of two probes contacting a single terminal and having a test voltage applied.

15 **Fig. 4** shows a top view of the chip terminal of **Fig. 1** contacted by three exemplary probe segments according to the second embodiment of the present invention.

20 **Fig. 5** shows a front view of the chip terminal of **Fig. 1** contacted by three exemplary probe segments according to **Fig. 3**.

**Fig. 6** shows a three-dimensional view of the chip terminal of **Fig. 1** contacted by three exemplary probe segments according to **Fig. 3**.

25 **Fig. 7** shows a three-dimensional view of the chip terminal of **Fig. 1** with plastic deformations resulting from a contacting by three exemplary probe segments according to **Fig. 3**.

30 **Fig. 8** shows a block diagram illustrating the steps corresponding to the second embodiment of the invention.

**Fig. 9** shows a simplified graph of constant and variable voltage drops according to first, second, and third path resistance measured by applying a test voltage.

5

#### DETAILED DESCRIPTION

Although the following detailed description contains many specifics for the purposes of illustration, anyone of ordinary skill in the art will appreciate that many variations and alterations to the following details are within the scope of the invention. Accordingly, the following preferred embodiment of the invention is set forth without any loss of generality to, and without imposing limitations upon, the claimed invention.

**Fig. 1** shows a top view of a terminal **1** placed on a chip segment **2**. The chip segment **2** represents electronic circuit chips as are well known to those skilled in the art. For the purpose of simplicity, the chip segment **2** is illustrated having only one terminal **1**. It is clear, that a chip represented by the chip segment **2** may have any number of terminals in multiple representation of the terminal **1**.

25

The terminal **1** has an exemplary configuration of a solder bump as they are known to those skilled in the art. The solder bump has a terminal height **1H** (see **Fig. 5**) and a terminal surface radius **1R** (see **Fig. 5**). It is noted that the core of the invention is not limited by the shape or configuration of the terminal **1**. Moreover, the terminal **1** may have any shape or configuration suitable for being

30

contacted by two or more probe tips **27A**, **27B** (see **Figs. 5** and **6**) like, for example, flat terminals or solder balls.

The terminal **1** has a terminal diameter **1D** within which a probe target area **3** having the probe target diameter **3D** is shown. The terminal **1** may be a rotationally symmetric terminal like for instance a solder ball or solder bump as are well known to those skilled in the art. In that case, the terminal center **TC** may be a rotational axis of the non-planar structure of the terminal **1**. It is noted that the scope of the invention is not limited to any specific shape of configuration of the terminal **1**, which may be planar as well.

The probe target area **3** is the area wherein a conventional probe tip (not shown) is brought into contact with its center during the testing of the chip. The probe target diameter **3D** is defined in correspondence with the terminal diameter **1D** to reassure reliable contact of probe tips **27A**, **27B** (see **Fig. 5, 6**) and the terminal **1**. Positioning tolerances of the tested chip and assembly tolerances of the probe tips **27A**, **27B** within the probe apparatus are adjusted to the probe target diameter **3D**. The smaller the probe target diameter **3D** relative to the terminal diameter **1D**, the more continuous a probe tip contacting quality between the probe tips **27A**, **27B** and the terminal **1**. Scrubbing of the probe tip **27A**, **27B** may be performed within the probe target area **3**.

**Fig. 2** shows a top view of the terminal **1** being contacted by first and second probes **5A**, **5B** according to the first embodiment of the invention. First and second probes **5A**,



5B have a common contacting center 9C, which is shown in a position within the probe target area 3. For the sole purpose of general understanding, the common contacting center 9C is shown in an offset distance 9 relative to the terminal center TC, which is also the center of the probe target area 3. It is clear that the common contacting center 9C may be positioned at any location within the probe target area 3 during a real life testing.

First and second probes 5A, 5B are exemplarily shown as being essentially cylindrical and protruding in view direction. The first and second probes 5A, 5B represent in a simplified form buckling beam probes as are well known to those skilled in the art. It is noted that the scope of the invention is not limited to buckling beam probes having circular section shapes in their portions dedicated for contacting chip terminals. Moreover, the present invention extends to any probes having tips in a configuration that allows them to be contacted with a single chip terminal in a number of two or more. Never the less, buckling beams are the preferred selection for the individual probes 5A, 5B and 5C (see Figs. 4, 5, 6).

In Fig. 2, the probes 5A, 5B are shown with conductive cores 6A, 6B, and the insulation layers 7A, 7B. The conductive cores 6A, 6B have a core diameter 6D. The insulation layers 7A, 7B define the probe segment diameter 7D. The probes 5A, 5B are guided within a guiding boundary 4, which may be provided by a sheath as is well known to those skilled in the art. The guiding boundary has a maximum extension 4D, which is less than the probe target diameter 3D plus half of an array distance of multiple

representations of the terminal **1** arrayed on the chip represented by the chip segment **2**.

The insulation layers **7A, 7B** are configured to prevent the conductive cores **6A, 6B** from conductively contacting with each other.

**Fig. 3** shows a schematic front view of the probes **5A, 5B** contacting the terminal **1** and space transformer terminals **28A, 28B** of a space transformer **8**. The contacting of two individual probes **5A, 5B** with the single terminal **1** provides a test path between the terminals **28A, 28B** that does not pass through the tested chips circuitry. An electronic circuit **EC** may apply a test voltage **V+** and **V-** on the terminals **28A, 28B** and a path resistance **R** between the terminals **28A, 28B** is measured without affecting the circuit chip. The probes **5A, 5B** and the terminal **1** define a constant resistance portion of the path resistance. The interfaces **21A, 21B** between the probes **5A, 5B** and the terminal **1** define a variable resistance portion of the path resistance. In the case where the two probes are in a loose contact with the terminals **28A, 28B**, the variable resistance portion may be additionally defined by the interfaces **18A, 18B** between the upper probe ends **25A, 25B** and the terminals **28A, 28B**. The loose contact of the probe ends **25A, 25B** with the terminals **28A, 28B** may be a force induced contact established by the contact force induced by the terminal **1** onto the probe tips **27A, 27B** and opposed by the terminals **28A, 28B**. The loose contact may also be a friction based contact provided by a spring loaded fit of the upper probe ends **25A, 25B** within correspondingly caved terminals **18A, 18B**. During the circuit chip testing, the

operational signals **OS** are passing through the space transformer **8**, the probes **5A**, **5B**, the terminal **1**, the interfaces **18A**, **18B**, **21A**, **21B** and the chip represented by the chip segment **2**.

5

After measuring the path resistance, the probe apparatus may begin testing the circuit chip by transmitting and/or receiving operational signals via the probes **5A** and/or **5B** onto and/or away from the terminal **1**. The voltage levels  
10 of the operational signals are increased in correspondence to the half path resistance in order to compensate for a voltage drop of them along one of the probes **5A**, **5B**, the terminal **1**, one of the interfaces **21A**, **21B** and eventually one of the interfaces **18A**, **18B**. The operational signals  
15 may be directed through one or both probes **5A**, **5B**.

The measurement of the path resistance along the test path and the voltage level adjustment of the operational signals may be provided by electronic circuitry as is well known to  
20 those skilled in the art. This electronic circuitry may be part of the space transformer, or at any other location within the probe apparatus. It is noted that the core of the invention is not limited to a specific location or configuration of the electronic circuitry. Moreover, the  
25 electronic circuitry may be part of a separate apparatus operating in combination with the probe apparatus of the present invention.

The recognized path resistance may be further utilized to  
30 control other factors related to the testing and/or fabrication of the circuit chips tested by the inventive apparatus. For example, continuously and evenly changing

path resistance of all accessed terminals of a number of tested chips may be utilized as an indicator to adjust production settings related to the fabrication of the tested chips' terminals.

5

The recognized path resistance may also be utilized to derive information about the working condition of the probe apparatus itself. For example, discrepancies of several path resistances between individual probe groups may be used as indicator for deformations of probe tips or other developing functional distortions of the grouped probes. Path resistance discrepancies may also be utilized as indicator for necessary probe tip cleaning operation.

10

15

**Fig. 4** shows a top view of a second embodiment of the invention in which three probes **5A, 5B, 5C** are combined in a probe group dedicated for contacting the single terminal **1**. The third probe **5C** preferably conforms in its configuration to the first and second probes **5A, 5B**.

20

The teachings stated for the first embodiment may be applied to the second embodiment with following differences:

25

30

1. The presence of three probes **5A, 5B, 5C** provides for three individual path resistances rather than only one path resistance as described for the first embodiment. A first path resistance is provided along first and second probe **5A, 5B**, the terminal **1** and the corresponding interfaces. A second path resistance is provided along first and third probe **5A, 5C**, the terminal **1** and the corresponding interfaces. A third path resistance is provided along second and third

probe **5B**, **5C**, the terminal **1** and the corresponding interfaces. The three path resistances have a constant resistance portion and a variable resistance portion as described for the first embodiment.

2. The guiding boundary **14** may be circular in shape rather than a long hole as described for the guiding boundary **4**.

**Fig. 5** shows a front view of the second embodiment. For the purpose of simplicity, the probes **5A**, **5B**, **5C** are shown with their conductive cores **6A**, **6B**, **6C** being broken off along the breaking lines **17A**, **17B**, **17C** and the insulation layers **7A**, **7B**, **7C** are broken off along the breaking lines **16A**, **16B**, **16C**. The probe tips **27A**, **27B** are illustrated as they are impacting the terminal **1** due to a contact force with which the terminal **1** is pressed against them during the chip testing. The probe **5C** may also deform with its probe tip the terminal **1**, which is not visible in **Fig. 5** (and **Fig. 6**) since the probe **5C** is positioned behind the terminal contour having the radius **1R** and the height **1H**. The impacting of the probes **5A**, **5B**, **5C** results in plastic deformations **11A**, **11B**, **11C** (see **Fig. 7**).

The offset distance **9** results in differing impacting levels **15A**, **15B** of the probes **5A**, **5B**, **5C**. The impacting level of the probe **5C** is again not shown because of the reason described above. The probes **5A**, **5B**, **5C** are configured to allow sufficient suspension within the probe group in order to compensate for the differences of the impacting levels **15A**, **15B**.

**Fig. 6** shows a three-dimensional view from a low frontal viewpoint onto the three probes **5A, 5B, 5C** impacting the terminal **1**. **Fig. 6** illustrates more clearly the plastic deformations **11A, 11B**, resulting from the scrubbing of the probes **5A, 5B**. The probes **5A, 5B, 5C** are exemplarily illustrated in the **Figs. 5 and 6** with laterally exposed conductive cores **6A, 6B, 6C** in proximity to the probe tips **27A, 27B**. The core of the invention is not limited by a specific configuration of the probes **5A, 5B, 5C**. It is clear that the conductive cores **6A, 6B, 6C** may be insulated to the very tip of the probes **5A, 5B, 5C** or may have any other configuration suitable for multiple contacting of single chip terminals. For example, the probe tips **27A, 27B** and the probe tip of the probe **5C** may have a spherical shape rather than a cylindrical. The probe tips **27A, 27B** may be spherically formed by a short melting of them as is well known for the fabrication of contact pins. Spherically formed probe tips may provide a self centering effect on the probe group having three probes **5A, 5B, 5C**. As a result, lateral forces resulting from the offset distance **9** on the terminal **1** may be kept to a minimum.

**Fig. 7** shows a three dimensional view of the terminal **1** with the plastic deformations **11A, 11B, 11C**. The probes **5A, 5B, 5C** are hidden in order to illustrate the interfaces **21A, 21B, 21C** between the terminal **1** and the probes **5A, 5B, 5C**. The interfaces **21A, 21B, 21C** may impose varying interface resistances between the probe tips **27A, 27B** of the probes **5A, 5B, 5C** and the terminal **1**. The varying interface resistances may result from remaining oxide layers, which may not be fully removed by the probe tips' scrubbing as is well known to those skilled in the art.

In addition, the use of more than one, preferably more than two probes contacting the terminal **1** results in balanced lateral forces stemming from eventual off center contacting of the non planar terminal surface. In cases where a probe apparatus has to simultaneously contact and test a high number of terminals **1**, sum lateral forces are kept at a low level. In addition, the probe tips may have a spherical shape, which may increase a self centering effect of each probe group contacting single terminals.

**Fig. 8** shows a block diagram illustrating the steps corresponding to the second embodiment of the present invention. During a chip testing cycle, a number of chip terminals may be contacted by probe groups as shown by the step **61**. In the following steps **62A**, **62B**, **62C**, the first second and third path resistance are recognized by a resistance recognition means illustrated by the block **66**. In the following step **63**, first second and third path resistance are compared with each other. In a next step **64**, an absolute resistance values for the operational signal paths are derived from the step **63**, which is described below under **Fig. 9** in more detail. In a final step **65**, the voltage levels of the operational signals may be adjusted as is described for the first embodiment. The testing signals may be directed in fractions through one, two or all three operational signal paths corresponding to the probes **5A**, **5B**, **5C**. The voltage levels may be individually adjusted for one, two or all operational signal paths.

**Fig. 9** shows a simplified graph of voltage drops along the first, second and third test paths during the measurement of the first, second and third path resistances.

Illustrated are graph segments **C1**, **C5** representing the constant resistive elements terminal **1** and probes **5A**, **5B**, **5C**. Illustrated are also the graph segments **C11** representing the variable resistance elements, which are the interfaces **21A**, **21B**, **21C** and eventual the interfaces **18A**, **18B** and a corresponding interface between the probe **5C** and a terminal of the space transformer **8**.

The terminal **1** is illustrated with an exemplary voltage drop **R1**. The first, second and third probes **5A**, **5B**, **5C** are illustrated with an exemplary voltage drop **R5**. The first, second and third interfaces **21A**, **21B**, **21C** and eventual the interfaces **18A**, **18B** and a corresponding interface for the probe **5C** are illustrated with exemplary voltage drops **R21A**, **R21B**, **R21C**. Consequently, the first, second and third path resistances result in the first, second and third test voltage drops **R2**, **R3**, **R4** along their test paths.

The test voltage drops **R2**, **R3**, **R4** are associated with ohm's resistances. The resistances of the probes **5A**, **5B**, **5C** as well as the resistance of the terminal **1** are predetermined and constant. The constant resistances are therefore subtracted from the three path resistances. The remaining three variable resistance portions of the three path resistances are compared with each other. Following relation between the test voltage drops are defined:

$$R_{21A} + R_{21C} + R_1 + 2 * R_5 = R_4$$

$$R_{21B} + R_{21C} + R_1 + 2 * R_5 = R_3$$

$$R_{21A} + R_{21B} + R_1 + 2 * R_5 = R_2$$

From this follows:



$$R_{21A} = R_4 - R_1 - 2 * R_5 - R_{21C}$$

$$R_{21C} = R_3 - R_1 - 2 * R_5 - R_{21B}$$

$$R_{21B} = R_2 - R_1 - 2 * R_5 - R_{21A}$$

This allows the following substitutions, which result in absolute values of the individual variable resistance portions derived solely from the constant resistance portions **R1**, **R5** and the three path resistances **R2**, **R3**, **R4**.

$$R_{21C} = R_3 - R_2 + R_{21A}$$

$$R_{21A} = (R_4 - R_1 - 2 * R_5 - R_3 + R_2) / 2$$

The equations are only shown for an absolute value of **R21A**. It is clear to one skilled in the art how to derive absolute values for **R21B** and **R21C** from the equations above. An algorithm according to the equations above may be implemented in the electronic circuit as is well known to those skilled in the art in order to derive absolute values for each operational signal path resistance associated to each of the three probes **5A**, **5B**, **5C**.

Further more, the core of the invention may be applied to any apparatus having probes contacting terminals for transferring electrical signals.

It is noted, that the scope of the invention is not limited to a specific number of probes contacting single terminals.

The invention may be utilized to provide, for example, four probes for testing contact resistance of a single terminal in accordance with 4-Wire Ohm's Measurement as is well known to those skilled in the art.

Accordingly, the scope of the present invention described in the specification above, is set forth by the following claims and their legal equivalent:

	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------